



EPA Tier 3 Emission Data
Fire Pump NSPS Compliant

CFP15E-F30 Fire Pump Driver

Type: 4 Cycle; In-Line; 6 Cylinder
Aspiration: Turbocharged, Charge Air Cooled

15 PPM Diesel Fuel																	
RPM	BHP	Fuel Consumption		D2 Cycle Exhaust Emissions										Exhaust			
		Gal/Hr	L/hr	Grams per BHP - HR					Grams per kW - HR					Temperature		Gas Flow	
				NMHC	NOx	NMHC+NOx	CO	PM	NMHC	NOx	NMHC+NOx	CO	PM	°F	°C	CFM	L/sec
1470	450	23.5	89.0	0.086	2.661	2.747	0.671	0.078	0.116	3.568	3.684	0.900	0.105	969	521	2740	1293
1760	542	26.5	100.3											905	485	3164	1493
1900	575	27.9	105.6											906	486	3328	1571
2100	575	29.1	110.2											884	473	3577	1688
2250	448	23.1	87.4											778	414	3756	1773

The emissions values above are based on CARB approved calculations for converting EPA (500 ppm) fuel to CARB (15 ppm) fuel.

300-500 PPM Diesel Fuel																	
RPM	BHP	Fuel Consumption		D2 Cycle Exhaust Emissions										Exhaust			
		Gal/Hr	L/hr	Grams per BHP - HR					Grams per kW - HR					Temperature		Gas Flow	
				NMHC	NOx	NMHC+NOx	CO	PM	NMHC	NOx	NMHC+NOx	CO	PM	°F	°C	CFM	L/sec
1470	450	23.5	89.0	0.104	2.781	2.886	0.671	0.089	0.14	3.730	3.870	0.900	0.120	969	521	2740	1293
1760	542	26.5	100.3											905	485	3164	1493
1900	575	27.9	105.6											906	486	3328	1571
2100	575	29.1	110.2											884	473	3577	1688
2250	448	23.1	87.4											778	414	3756	1773

QSX15 Base Model Manufactured by Cummins Inc.
- Using fuel rating 10663

Reference EPA Standard Engine Family: 8CEXL015AAH

No special options needed to meet current regulation emissions for all 50 states

Test Methods:

EPA/CARB Nonroad emissions recorded per 40CFR89 (ref. ISO8178-1) and weighted at load points prescribed in Subpart E, Appendix A, for Constant Speed Engines (ref. ISO8178-4, D2).

Diesel Fuel Specifications:

Cetane Number: 40-48
Reference: ASTM D975 No. 2-D

Reference Conditions:

Air Inlet Temperature: 25°C (77°F)
Fuel Inlet Temperature: 40°C (104°F)
Barometric Pressure: 100 kPa (29.53 in Hg)
Humidity: 10.7 g/kg (75 grains H₂O/lb) of dry air; required for NOx correction

Restrictions: Intake Restriction set to a maximum allowable limit for clean filter; Exhaust Back Pressure set to maximum allowable limit.

Tests conducted using alternate test methods, instrumentation, fuel or reference conditions can yield different results.